

SMB AI-Systems & High-Speed Interconnect

100ge pigtail fiber



100ge pigtail fiber



QSFP-ZR4-100G The QSFP28-100G-ZR4-S Module is designed for use in 100GBASE Ethernet throughput up to 80km over single mode fiber (SMF) using a wavelength of 1310nm via duplex LC ...



Leviton fiber optic pigtail kits are a good solution for mechanical or fusion splicing applications. Available in a range of multimode and single-mode fibers with SC, ST or LC connectors. Our premium pigtails ...



ST Fiber Optic Pigtail: ST pigtail connector is the most popular connector for multimode fiber optic LAN applications. It has a long 2.5mm diameter ferrule made of ceramic (zirconia), stainless alloy or plastic.



FTLC9558REUM 100G QSFP28 pigtail transceiver modules are designed for use in 100 Gigabit Ethernet links over multimode fiber and can endure liquid immersion environment. They are ...



These modules are designed to operate over multimode fiber systems using a nominal wavelength of 850nm. The electrical interface uses a 38 contact edge type connector.



Standard Tx output power (-8dBm), 100GE & OTU4, C-temp, 0°C to 70°C, CMIS. ...



100G QSFP28 CWDM4 4x 25G NRZ QSFP-100G-CWDM4-S 1310nm 2km Duplex LC/UPC Module, Cisco.



The FTLC9558REUM 100G QSFP28 pigtail transceiver modules are engineered for application in 100 Gigabit Ethernet connections over multimode fiber and are capable of withstanding environments ...




It only needs a duplex single mode fiber cable to connect two 100G CWDM4 optical modules. At present, CWDM4 links are used in both 100G CFP4 or the QSFP28 optical transceivers.



Fortinet's transceivers have been purpose-built and tested to work with Fortinet equipment, ensuring that your network is as stable and robust as possible, and taking the guesswork out of selecting ...



Standard Tx output power (-8dBm), 100GE & OTU4, C-temp, 0°C to 70°C, CMIS. Built around Coherent Steelerton DSP, the 100G ZR QSFP28-DCO transceiver is fully compliant to the IEEE 802.3™ -2022 ...



Pigtail kits shall be available with 900-micron tight buffer LSZH coating and 250-micron coated fiber. Pigtail kits shall be individually packaged with part numbers, descriptions, optical performance, and ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://samastersbaseball.co.za>

Email: sales@samastersbaseball.co.za

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

