

## Dimensions of the splice box

### Ordering information

NO.	1	2	3	4
Model	FS4M1	FS8M2	FS12M3	FS16M4
Product name	Patch Panel	Patch Panel	Patch Panel	Patch Panel
Illustration				
HU	1	2	3	4
Maximum number of cores	96	192	288	384
Product size (excluding modules and adapters)	482.6*208.7*43.7mm	482.6*208.7*88.1mm	482.6*208.7*132.5mm	482.6*208.7*177.7mm
Standard color code	RAL9005	RAL9005	RAL9005	RAL9005

## Dimensions of the splice box



This document provides dimensions, illustrations, and ordering information for surface-operable, primary, electric underground equipment and splice enclosures including frame and cover assemblies.



So you're splicing in this box? The minimum (between the opposite ends of entry) would be  $8 \times 5 = 40$ ". I would opt for a 48" minimum just to make the splicing easier.



With standard and customizable options, these vaults are the perfect example of value-added engineering with preinstalled equipment and accessories saving time and money on your next project.



1075KWHH ESS

Specifications General Orenco splice boxes come standard with one to six watertight cord grips. Included are waterproof wire nuts, a sealing gasket, and four stainless steel lid screws. Splice boxes ...



gasket, and four stainless steel lid screws. Splice boxes also come standard with 1/2-in. (13-mm) cord grips. and a 15/8-in. (41-mm) long conduit coupling. Large 3/4-in. (19-mm) cord grips and 31/4-in. (83 ...



SEC splice boxes are designed to fit most conductors from number 10 to 2/0, depending on insulation thickness, and will provide connections for up to four wires or any combination.



Fibre Optic (FO) distribution box; panel mounting; compact dimensions, lockable, max. capacityx of 8 splicing cartridges ore one distribution plate  
product information (PDF)



This family of enclosures provides improved splice management and access, a variety of modular cable port accessories and increased splice storage density in several housing sizes and capacities.



Underground concrete enclosure that houses utility equipment. Three blank plastic nameplates with one marked PG& E High Voltage non-slip hinged aluminum cover. PG& E code: 025601. Product ...



Aerial Junction Boxes Unless otherwise shown in the Plans, provide aerial junction boxes with minimum inside dimensions of 8 inches wide by 8 inches long and at least 3 inches deep.



Internal Splice Boxes Applications as effluent pumps and float switches. They conform to UL 514C, CSA C22.2 N . 85 1968, and meet UL Type 4X rating. Cord grips can with-stand tem eratures of up to 212° ...

## Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://samastersbaseball.co.za>

Email: [sales@samastersbaseball.co.za](mailto:sales@samastersbaseball.co.za)

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

