

Power Equipment Relay Protection Devices



Overview

Electromechanical relays can be classified into several different types as follows: "Armature"-type relays have a pivoted lever supported on a hinge or knife-edge pivot, which carries a moving contact. These relays may work on either alternating or direct current, but for alternating current, a shading coil on the pole is used to maintain contact force throughout the alternating current cycle. Because the air gap between the fixed coil and the moving armature becomes much smaller when the relay has operated, the current required to maintain the relay closed is much smaller than the current to first operate it. The "returning ratio" or "differential" is the measure of how much the current must be reduced to reset the relay. A. In, a protective relay is a device designed to trip a when a is detected. The first protective relays were electromagnetic devices, relying on coils operating on moving parts to provide detection of abnormal operating conditions such as over-current,, reverse flow, over-frequency, and under-frequency. Microprocessor-based

digital protection relays now emulate the original devices, as well as providing types of protection and supervision impractical with electromechanical relays. provide only rudimentary indication of the location and origin of a fault. In many cases a single microprocessor relay provides functions that would take two or more electromechanical devices. By combining several functions in one case, numerical relays also save capital cost and maintenance cost over electromechanical relays. However, due to their very long life span, tens of thousands of these "silent sentinels" are still protecting transmission lines and electrical apparatus all over the world. Important transmission lines and generators have cubicles dedicated to protection. Electromechanical protective relays operate by either, or. Unlike switching type electromechanical with fixed and usually ill-defined operating voltage thresholds and operating times, protective relays have well-established, selectable, and adjustable time and current (or other operating parameter) operating characteristics. Protection relays may use arrays of, shaded-pole, magnets, operating and restraint coils, solenoid-type operators, telephone-relay contacts, and phase-shifting networks. Protective relays can also be classified by the type of measurement they make. A protective relay may respond to the magnitude of a quantity such as voltage or current. Induction relays can respond to the product of two quantities in two field coils, which could for example represent the power in a circuit. "It is not practical to make a relay that develops a torque equal to the quotient of two a.c. quantities. This, however is not important; the only significant condition for a relay is its setting and the setting can be made to correspond to a ratio regardless of the component values over a wide range." Several operating coils can be used to provide "bias" to the relay, allowing the sensitivity of response in one circuit to be controlled by another. Various combinations of "operate torque" and "restraint torque" can be produced in the relay. By use of a permanent magnet in the, a relay can be made to respond to current in one direction differently from in another. Such are used on direct-current circuits to detect, for example, reverse current into a generator. These relays can be made bistable, maintaining a contact closed with no coil current and requiring reverse current to reset. For AC circuits, the principle is e. The various protective functions available on a given relay are denoted by standard. For example, a relay including function 51 would be a timed overcurrent protective relay. An overcurrent relay is a type of protective relay which operates when the load current exceeds a pickup value. It is of two types: instantaneous over current (IOC) relay and definite time overcurrent (DTOC) relay. The is 50 for an IOC relay or a DTOC relay. In a typical application, the over current relay is connected to a current transformer and calibrated to operate at or above a specific current level. When the relay operates, one or more contacts will operate and energize to trip a circuit breaker. The DTOC relay has been used extensively in the United Kingdom but its inherent issue

of operating slower for faults closer to the source led to the development of the IDMT relay. A definite time over-current (DTOC) relay is a relay that operates after a definite period of time once the current exceeds the pickup value. Hence, this relay has current setting range as well as time setting range. An instantaneous over-current relay is an overcurrent relay which has no intentional time delay for operation. The contacts of the relay are closed instantly when the current inside the relay rises beyond the operational value. The time interval between the instant pick-up value and the closing contacts of the relay is very low. It has low operating time and starts operating instantly when the value of current is more than the relay setting. This relay operates only when the impedance between the source and the relay is less than that provided in the section. An inverse-time over-current (ITOC) relay is an overcurrent relay which operates only when the magnitude of their operating current is inversely proportional to the magnitude of the energize quantities. Th. Relays can also be classified by their type of power source. • Self-powered relays operate on energy derived from the protected circuit, such as through the current transformers used to measure line current. Self-powered relays are advantageous in terms of cost and reliability as they do not require a separate power supply. • Auxiliary-powered relays rely on a battery or external AC supply. Some relays can use either AC or DC. The auxiliary supply must be highly reliable during a system fault to ensure the relay can operate. • Dual-powered relays are powered by the protected circuit and through an auxiliary power source which acts as a backup.

Power Equipment Relay Protection Devices



GE Vernova's Protection, Control, and Metering solutions deliver precise, high-performance automation for today's evolving grid. From advanced relays to multifunction meters, our portfolio helps utilities ...



Protective relays are essential in power systems to detect faults, isolate problem areas, and prevent widespread damage. Their use spans high-voltage transmission, industrial machinery, ...




Protective relays are critical components in power systems, providing essential protection for various elements such as generator sets, outgoing feeder and load networks, and incoming utility ...



Protective relays and devices have been developed over 100 years ago to provide “lastline” of defense for the electrical systems. They are intended to quickly identify a fault and isolate it so the balance of ...



Protective relays are one of the critical components of the electrical power grid that serve to detect defective equipment or other dangerous or intolerable conditions and can either initiate or permit ...



Protective relays play a vital role in safeguarding electrical systems, ensuring safety, and preventing costly equipment damage. These devices are essential components in various ...



Electromechanical protective relays at a hydroelectric generating plant. The relays are in round glass cases. The rectangular devices are test connection blocks, used for testing and isolation of ...



Learn about protective relays, their working principle, types, and applications in power systems. Discover how relays protect transformers, generators, and transmission lines from faults.



Protection Relays: Protection relays monitor the electrical network and initiate the tripping of circuit breakers when they detect anomalies, critical for mitigating damage during faults.



Protect critical components in your power system with a wide range of SEL protective relays covering applications and use cases from low to high-voltage protection.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://samastersbaseball.co.za>

Email: sales@samastersbaseball.co.za

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

