

Removing the top cover of the network cabinet



Overview

Remove top Cover Plates of Rear Side Panel by pulling plunger slightly to release Cover Plate. (Bumper Plate will be to center of cabinet. If any devices are installed to the extension panels, remove them (see Remove a 0U PDU or Remove a 1U PDU or console switch from the rack side). To remove the side covers from a standard rack, complete the following steps: Unlock the button lock. Ensure that you have the following parts and tools available to power off the switch: A cable to connect the external management device to the console port (CONSOLE) or management port (< . >) on the primary Routing Engine module (RE module). To power off the switch: Connect a management console. If you need to extend the fiber you can get a fiber SC coupler and single mode fiber cable with SC APC ends. to/3P9ne79 Patch cable example <https://amzn.to/3Ns5Uc6> Covers of nh20 may have a small screw on the bottom keeping it on. Make sure that the appliance cover.

Removing the top cover of the network cabinet




Unlock the side cover with the key. Press on the two latches on both sides of the cover to disengage it from the rack. Rotate the top of the side cover away from the rack, and remove it.



Screws for top and bottom plate are middle just above/below network jacks side of the router. The wall plate will have 2 screws going through from the router you can see after removing the top cover. It is ...



If you cannot use a mechanical lift to remove an EX9204 switch from a rack or a cabinet (the preferred method), you can remove it manually.



TOP CAP REMOVAL INSTRUCTIONS -Remove Torx screws (use T25 Torx bit) -Carefully remove Top Cap from Cabinet Frame



Rear Side Panel with Bumper Plate to be installed first. Remove top Cover Plates of Rear Side Panel by pulling plunger slightly to release Cover Plate. (Bumper Plate will be to center of cabinet.) Tilt the ...



While holding Between Cabinet Bracket, attach Seal Cover to the Between Cabinet Bracket using M5 Torx Screw. Attach 25mm x 50mm Foam Seal to the bottom of the Seal Cover.



About this task The standard rack comes with the side covers installed. Remove the side covers from the rack before you install or remove optional devices.



Remove the appliance from the cabinet or rack to access the top cover. Make sure that the appliance cover latch is not locked. If necessary, turn the blue plastic latch lock one-quarter turn in ...



If any devices are installed to the extension panels, remove them (see Remove a 0U PDU or Remove a 1U PDU or console switch from the rack side). Remove the two hinges, two door stops, and the door ...



Once ganged the angle required to remove the door changes quite a bit. It's much shallower. To remove the doors once the enclosures are bayed please follow these directions: 1) ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://samastersbaseball.co.za>

Email: sales@samastersbaseball.co.za

Phone: +27 63 874 2095

Address: 15 Innovation Drive, Technopark, Stellenbosch, 7600, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

